



Features

- Contemporary lighting family includes sconce, bollard and path light in new Graphite finish
- Low-VOC painted aluminum housing with polycarbonate lens
- 3000K color temperature with 90+ CRI
- cETLus Listed for wet locations
- 30,000 hours rated life

Available Finishes



Graphite

Listing / Ratings



FRAMEWRX Stage Series

This structural looking favorite is smart and tailored in appearance, while providing a patterned effect as the light hits the path/ground/wall. The family casts 3000K warm white LED light for easy integration into residential landscape lighting designs. The bollard has 120-277V AC input and a 39.4" height for commercial applications.

Technical Information

Series	STAGE
Input Voltage	120-240V AC / 120-277V AC / 12V AC/DC
CCT	3000K (WW)
CRI	90+
Wattage	7.5W / 10W / 10W
Lumens	up to 450Lm
Beam Angle	120°
Dimmable	N/A
Mounting	Surface Mount
Rating	cETLus Listed (wet location)
Rated Life	30,000 hrs

FRAMEWRX Stage Series



Stage Bollard Light
BOL-STAGE-GT (120-277V / 10W / 450Lm)
 5-15/16"W x 2-3/8"D x 39-13/32"H



Stage Wall Sconce
SCO-STAGE-GT (120-240V / 7.5W / 240Lm)
 7-3/16"W x 5-27/32"D x 5-1/4"H



Stage Path Light
PATH-STAGE-GT (12V / 10W / 450Lm)
 5-15/16"W x 2-3/8"D x 18"H

PATH-SMS
 Soil mounting stake for FrameWRX path lights

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

STAGE SERIES
 ARCHITECTURAL LIGHTING

POWER SUPPLIES