



Instructions for 50030, 31,32,33,34,35

(1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE & PHILIPS SCREW DRIVER
- ❖ ADJUSTABLE WRENCH
- ❖ STEP LADDER
- ❖ WIRE CUTTERS
- ❖ WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE

Attention:

Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure. For mounting to a PVC or Plastic Box do not use supplied crossbar or attach directly to the junction box. The recessed holes located on the outer sides of the fixture should be utilized for mounting the fixture directly to the ceiling, utilizing the correct screws and anchors (not supplied).
4. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- ❖ Mounting Hardware Package
- ❖ Glass Diffuser
- ❖ Fixture Assembly
- ❖ 1 x 150W/T-3/118mm Lamp (model 50034)

(4) PREPARE THE FIXTURE

Refer to figure 1 for illustration of fixture parts and assembly.


1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Attach the supplied short screws to the crossbar and fasten the crossbar to the junction box, ensuring that the nipples from the base of the fixture hang down (towards the ground).

Please note do not attach this fixture directly to a PVC or Plastic Junction box see point 3 of General section

1. Attach the ground wire from the fixture to the outlet box ground terminal (or to the box ground wire). Connect the fixture wires to the appropriate electrical supply wires from the outlet box using the supplied wire connectors. Secure wire connectors with UL listed electrical tape. Tuck wires carefully into outlet box.
2. Secure the base to the J-box by placing the nipples from the crossbar through the designated holes in the base. Secure with the supplied nuts.
3. Secure the glass diffuser to base of the fixture, by aligning the screws in the diffuser with designated holes in the base of the fixture. Tighten the screws with a coin. Ensure that screws are tight enough to secure glass but not to inflict damage to the glass diffuser.
4. Restore electricity and check the operation of your new lighting fixture.

CAUTION:

- **Do Not Operate the Lighting Fixture close to any Combustible Material.**



access

L I G H T I N G

Model(s): 50030, 50031, 50032, 50033, 50034, 50035

